

AVAILABLE FROM

<http://www.superbrightleds.com/leds.htm>

PART NUMBER	COLOR	LENS COLOR	LUMINOUS INTENSITY(mcd)	VIEWING ANGLE	(\ddot{y} D) WAVE LENGTH	SIZE
RL5-W15120	White	clear	1500	120°	x=.29;y=.30	T-1 3/4
RL5-W2545	White	clear	2500	45°	x=.27;y=.27	T-1 3/4
RL5-W8045	White	clear	8000	45°	x=.29;y=.28	T-1 3/4
RL5-W3030	White	clear	3000	30°	x=.27;y=.27	T-1 3/4
RL5-W18030	White	clear	18000	30°	x=.27;y=.27	T-1 3/4
RL5-W5020	White	clear	5000	20°	x=.31;y=.32	T-1 3/4
RL5-W6018	White	clear	6000	18°	x=.31;y=.32	T-1 3/4
RL5-W6030	White	clear	6000	30°	x=.30;y=.32	T-1 3/4
RL5-W10015	White	clear	10000	15°	x=.27;y=.28	T-1 3/4
RL5-W18015	White	clear	18000	15°	x=.29;y=.29	T-1 3/4
RL5-WW7035	Warm White	clear	7000	35°	x=.44;y=.41	T-1 3/4
RL5-B2545	Blue	clear	2500	45°	472 nm	T-1 3/4
RL5-B4630	Blue	clear	4600	30°	472 nm	T-1 3/4
RL5-B2430	Blue	clear	2400	30°	470 nm	T-1 3/4
RL5-B5515	Blue	clear	5500	15°	470 nm	T-1 3/4
RL5-G8045	Green	clear	8000	45°	525 nm	T-1 3/4
RL5-G7532	Green	clear	7500	32°	525 nm	T-1 3/4
RL5-G5023	Green	clear	5000	23°	524 nm	T-1 3/4
RL5-G8020	Green	clear	8000	20°	525 nm	T-1 3/4
RL5-G13008	Green	clear	13000	8°	525 nm	T-1 3/4
RL5-A7032	Aqua	clear	7000	32°	507 nm	T-1 3/4
RL5-A9018	Aqua	clear	9000	18°	505 nm	T-1 3/4
RL5-RD1560	Red	diffused	1500	60°	628 nm	T-1 3/4
RL5-R3545	Red	clear	3500	45°	628 nm	T-1 3/4
RL5-R8030	Red	clear	8000	30°	630 nm	T-1 3/4
RL5-R5015	Red	clear	5000	15°	631 nm	T-1 3/4
RL5-R12008	Red	clear	12000	8°	627 nm	T-1 3/4
RL5-R1330	Red	clear	1300	30°	660 nm	T-1 3/4
RL5-R2415	Red	clear	2400	15°	660 nm	T-1 3/4
RL5-Y3545	Yellow	clear	3500	45°	590 nm	T-1 3/4
RL5-Y5030	Yellow	clear	5000	30°	595 nm	T-1 3/4
RL5-Y3230	Yellow	clear	3200	32°	591 nm	T-1 3/4
RL5-Y4523	Yellow	clear	4500	23°	592 nm	T-1 3/4
RL5-Y5615	Yellow	clear	5600	15°	593nm	T-1 3/4
RL5-Y10008	Yellow	clear	10000	8°	588 nm	T-1 3/4
RL5-O4030	Orange	clear	4000	30°	605 nm	T-1 3/4
RL5-O5015	Orange	clear	5000	15°	605 nm	T-1 3/4
RL5-V1015	Violet	clear	1000	15°	420 nm	T-1 3/4
RL5-UV2030	UV	clear	20 mW	30°	405 nm	T-1 3/4
RL5-UV1230	UV	clear	12 mW	30°	400 nm	T-1 3/4
RL5-UV1215	UV	clear	12 mW	15°	400 nm	T-1 3/4
RL5-IR2730	IR	clear	27mW/sr	30°	945 nm	T-1 3/4
RL5-IR2030	IR	clear	20mW/sr	30°	880 nm	T-1 3/4
RL5-RGB	TriColor	clear	varies	15°	Full Color	T-1 3/4